



Scottoil: Aprilia RSV / R1000 Mille, SL 1000 Falco & Tuono Installation Guide for Aprilia RSV / R 1000 Mille, SL1000 Falco & Tuono.



Note: The HCR (sold separately) is no compatible with Falco models



For **1998** models, underneath the tank is a vacuum pipe, as shown on the left, cut into this pipe, and insert the T-Piece from the Scottoil kit. Then press the Damper Elbow (part no. 4) onto the third leg of the tee.

For **00-03** models & **Tuono pre 06**, there is a rubber bung over a spigot on the inlet tract, as shown below left. Remove this bung and then press the Damper Elbow, part number 4, onto the spigot.

For **2004** models, there is also a vacuum pipe under the tank - cut into this pipe, insert the T-Piece as shown, and fit the Damper Elbow.



The RMV can be mounted to the frame, as shown left.

The more vertical the RMV the better and remember to avoid exhaust and engine components.

For further information, see our easy step installation guide – 'RMV Positions, General'.

The Dispenser Assembly is mounted using Dispenser Mounting sleeves, glue and cable ties. **For 2004 RSVR Mille, you will require an adapter kit (free of charge from Scottoil)** It is not in the basic Mk 7 Kit & is shown below left & below.

The nib should feed the sprocket between the 6 & 7 o'clock positions.



If you have any further comments or queries, and are unable to resolve them using our website, please do not hesitate to call technical on 0141 955 1100 or email technical@scottoiler.com for assistance. Thank you.

Scottoil Ltd. 2 Riverside, Milngavie, Glasgow, G62 6PL Tel. 0141 955 1100 Fax. 0141 956 5896 www.scottoiler.com

